

COUPLINGS & CLAMPS

Reducing male-to-male stainless steel camlock adaptor

Reducing male-to-male stainless steel camlock adaptor for cam-and-groove hose and pipe connections. Select the size, material and interface for the complete connection.

Application: Application-led selection for the specified operating conditions.

Ordering references: SAS040X050 / SAS050X080 / SAS080X100

316 stainless camlock male male reducing

Part code	Material	End 1 nominal inch	End 2 nominal inch
SAS040X050	Stainless steel 316	1.5	2.0
SAS050X080	Stainless steel 316	2.0	3.0
SAS080X100	Stainless steel 316	3.0	4.0

316 stainless camlock male male reducing. Weld-end compatibility, pipe schedule and weld procedure must match the selected assembly. No pressure rating is transferred from another camlock construction. Confirm both end sizes for SAS125 and SAS150 before manufacture.

Application & quotation checklist

Coupling type, size and mating half; Medium, pressure and temperature; Body material and seal compound; Hose tail, thread, flange or weld connection

Request a quotation

admin@africanhosesolutions.co.za | 010 065 3872

Provide the part code, size, quantity, required configuration and application. Include a drawing or photograph where available.

Ratings apply only to the specified product and configuration. Confirm fluid compatibility, temperature, pressure transients, installation and complete assembly suitability. Ordering references do not establish interchangeability.