

## COUPLINGS &amp; CLAMPS

# Camlock type DP - male dust plug

Camlock type DP - male dust plug for cam-and-groove hose and pipe connections. Select the size, material and interface for the complete connection.

**Application:** Application-led selection for the specified operating conditions.

Available configurations: Aluminium; Brass; Polypropylene; Stainless steel 316

**Ordering references:** DPA050 / DPA075 / DPA100 / DPA125 / DPA150 / DPA200 / DPA250 / DPA300 / DPA400 / DPA500 / DPA600 / DPA800 / DPB050 / DPB075 / DPB100 / DPB125 / DPB150 / DPB200 / DPB250 / DPB300 / DPB400 / DPB500 / DPB600 / DPP050 / DPP075 / DPP100 / DPP125 / DPP150 / DPP200 / DPP250 / DPP300 / DPP400 / DPS050 / DPS075 / DPS100 / DPS125 / DPS150 / DPS200 / DPS250 / DPS300 / DPS400 / DPS500 / DPS600

## 316 stainless camlock type DP

| Part code | Material            | Nominal size inch | Metric designation mm |
|-----------|---------------------|-------------------|-----------------------|
| DPS050    | Stainless steel 316 | 0.5               | 12.0                  |
| DPS075    | Stainless steel 316 | 0.75              | 20.0                  |
| DPS100    | Stainless steel 316 | 1.0               | 25.0                  |
| DPS125    | Stainless steel 316 | 1.25              | 32.0                  |
| DPS150    | Stainless steel 316 | 1.5               | 40.0                  |
| DPS200    | Stainless steel 316 | 2.0               | 50.0                  |
| DPS250    | Stainless steel 316 | 2.5               | 65.0                  |
| DPS300    | Stainless steel 316 | 3.0               | 80.0                  |
| DPS400    | Stainless steel 316 | 4.0               | 100.0                 |
| DPS500    | Stainless steel 316 | 5.0               | 125.0                 |
| DPS600    | Stainless steel 316 | 6.0               | 150.0                 |

316 stainless camlock type DP. Pressure bands apply only to these standard 316 stainless configurations; temperature and medium conditions require confirmation. Dust caps and plugs protect disconnected ends; pressure-closure suitability requires separate confirmation. Nominal metric and inch designations are identifiers, not measured passage dimensions.

## 316 stainless camlock type DP - construction & conditions

| Parameter     | Specification                        |
|---------------|--------------------------------------|
| Arm material  | Stainless steel                      |
| Standard seal | NBR option; verify selected compound |

316 stainless camlock type DP. Pressure bands apply only to these standard 316 stainless configurations; temperature and medium conditions require confirmation. Dust caps and plugs protect disconnected ends; pressure-closure suitability requires separate confirmation. Nominal metric and inch designations are identifiers, not measured passage dimensions.

## Ordering configurations

| Part code | Configuration                    | Material  | Nominal size | Listed pressure (bar)                              |
|-----------|----------------------------------|-----------|--------------|----------------------------------------------------|
| DPA050    | Camlock type DP - male dust plug | Aluminium | 0.5 in       | Confirm pressure-service approval for this closure |
| DPA075    | Camlock type DP - male dust plug | Aluminium | 0.75 in      | Confirm pressure-service approval for this closure |

## Ordering configurations

| Part code | Configuration                    | Material      | Nominal size | Listed pressure (bar)                              |
|-----------|----------------------------------|---------------|--------------|----------------------------------------------------|
| DPA100    | Camlock type DP - male dust plug | Aluminium     | 1 in         | Confirm pressure-service approval for this closure |
| DPA125    | Camlock type DP - male dust plug | Aluminium     | 1.25 in      | Confirm pressure-service approval for this closure |
| DPA150    | Camlock type DP - male dust plug | Aluminium     | 1.5 in       | Confirm pressure-service approval for this closure |
| DPA200    | Camlock type DP - male dust plug | Aluminium     | 2 in         | Confirm pressure-service approval for this closure |
| DPA250    | Camlock type DP - male dust plug | Aluminium     | 2.5 in       | Confirm pressure-service approval for this closure |
| DPA300    | Camlock type DP - male dust plug | Aluminium     | 3 in         | Confirm pressure-service approval for this closure |
| DPA400    | Camlock type DP - male dust plug | Aluminium     | 4 in         | Confirm pressure-service approval for this closure |
| DPA500    | Camlock type DP - male dust plug | Aluminium     | 5 in         | Confirm pressure-service approval for this closure |
| DPA600    | Camlock type DP - male dust plug | Aluminium     | 6 in         | Confirm pressure-service approval for this closure |
| DPA800    | Camlock type DP - male dust plug | Aluminium     | 8 in         | Confirm pressure-service approval for this closure |
| DPB050    | Camlock type DP - male dust plug | Brass         | 0.5 in       | Confirm pressure-service approval for this closure |
| DPB075    | Camlock type DP - male dust plug | Brass         | 0.75 in      | Confirm pressure-service approval for this closure |
| DPB100    | Camlock type DP - male dust plug | Brass         | 1 in         | Confirm pressure-service approval for this closure |
| DPB125    | Camlock type DP - male dust plug | Brass         | 1.25 in      | Confirm pressure-service approval for this closure |
| DPB150    | Camlock type DP - male dust plug | Brass         | 1.5 in       | Confirm pressure-service approval for this closure |
| DPB200    | Camlock type DP - male dust plug | Brass         | 2 in         | Confirm pressure-service approval for this closure |
| DPB250    | Camlock type DP - male dust plug | Brass         | 2.5 in       | Confirm pressure-service approval for this closure |
| DPB300    | Camlock type DP - male dust plug | Brass         | 3 in         | Confirm pressure-service approval for this closure |
| DPB400    | Camlock type DP - male dust plug | Brass         | 4 in         | Confirm pressure-service approval for this closure |
| DPB500    | Camlock type DP - male dust plug | Brass         | 5 in         | Confirm pressure-service approval for this closure |
| DPB600    | Camlock type DP - male dust plug | Brass         | 6 in         | Confirm pressure-service approval for this closure |
| DPP050    | Camlock type DP - male dust plug | Polypropylene | 0.5 in       | Confirm pressure-service approval for this closure |

Ordering configurations

| Part code | Configuration                    | Material      | Nominal size | Listed pressure (bar)                              |
|-----------|----------------------------------|---------------|--------------|----------------------------------------------------|
| DPP075    | Camlock type DP - male dust plug | Polypropylene | 0.75 in      | Confirm pressure-service approval for this closure |
| DPP100    | Camlock type DP - male dust plug | Polypropylene | 1 in         | Confirm pressure-service approval for this closure |
| DPP125    | Camlock type DP - male dust plug | Polypropylene | 1.25 in      | Confirm pressure-service approval for this closure |
| DPP150    | Camlock type DP - male dust plug | Polypropylene | 1.5 in       | Confirm pressure-service approval for this closure |
| DPP200    | Camlock type DP - male dust plug | Polypropylene | 2 in         | Confirm pressure-service approval for this closure |
| DPP250    | Camlock type DP - male dust plug | Polypropylene | 2.5 in       | Confirm pressure-service approval for this closure |
| DPP300    | Camlock type DP - male dust plug | Polypropylene | 3 in         | Confirm pressure-service approval for this closure |
| DPP400    | Camlock type DP - male dust plug | Polypropylene | 4 in         | Confirm pressure-service approval for this closure |

Pressure values, where given, apply only to the listed configuration and its specified operating conditions. Confirm the complete assembly, temperature and conveyed medium. Dust closures require explicit pressure-service approval.

Application & quotation checklist

Coupling type, size and mating half; Medium, pressure and temperature; Body material and seal compound; Hose tail, thread, flange or weld connection

Request a quotation

admin@africanhosesolutions.co.za | 010 065 3872

Provide the part code, size, quantity, required configuration and application. Include a drawing or photograph where available.  
Ratings apply only to the specified product and configuration. Confirm fluid compatibility, temperature, pressure transients, installation and complete assembly suitability. Ordering references do not establish interchangeability.