COUPLINGS & CLAMPS

Stainless steel socket-weld camlock type A

Stainless steel socket-weld camlock type A for cam-and-groove hose and pipe connections. Select the size, material and interface for the complete connection.

Application: Application-led selection for the specified operating conditions.

Ordering references: ASW012 / ASW020 / ASW025 / ASW032 / ASW040 / ASW050 / ASW065 / ASW080 / ASW100

316 stainless camlock weldon a

Part code	Material	Nominal size inch	Weld end	Pipe schedule
ASW012	Stainless steel 316	0.5	Socket weld	Confirm
ASW020	Stainless steel 316	0.75	Socket weld	Confirm
ASW025	Stainless steel 316	1.0	Socket weld	40
ASW032	Stainless steel 316	1.25	Socket weld	40
ASW040	Stainless steel 316	1.5	Socket weld	40
ASW050	Stainless steel 316	2.0	Socket weld	40
ASW065	Stainless steel 316	2.5	Socket weld	40
ASW080	Stainless steel 316	3.0	Socket weld	40
ASW100	Stainless steel 316	4.0	Socket weld	40

316 stainless camlock weldon a. Weld-end compatibility, pipe schedule and weld procedure must match the selected assembly. No pressure rating is transferred from another camlock construction. Confirm both end sizes for SAS125 and SAS150 before manufacture.

Application & quotation checklist

Coupling type, size and mating half; Medium, pressure and temperature; Body material and seal compound; Hose tail, thread, flange or weld connection

Request a quotation

admin@africanhosesolutions.co.za | 010 065 3872

Provide the part code, size, quantity, required configuration and application. Include a drawing or photograph where available.

Ratings apply only to the specified product and configuration. Confirm fluid compatibility, temperature, pressure transients, installation and complete assembly suitability. Ordering references do not establish interchangeability.