

## COUPLINGS &amp; CLAMPS

# Instantaneous Fire-Hose Couplings

Instantaneous Fire-Hose Couplings for the specified hose, pipework and operating configuration. Select the size, material and interface for the complete connection.

**Application:** Application-led selection for the specified operating conditions.

**Ordering references:** MCB065/SET / MCBFXM065 / MCF065 / MCMB065 / MCA065X040/SET / MCA065X045/SET / MCA065X050/SET / MCA065X065/SET

**Ordering configurations**

| Part code      | Configuration                                      | Material               | Nominal size      | Listed pressure (bar)          |
|----------------|----------------------------------------------------|------------------------|-------------------|--------------------------------|
| MCB065/SET     | Bronze instantaneous fire hose coupling set        | Bronze                 | See configuration | Confirm for this configuration |
| MCBFXM065      | Bronze instantaneous female coupling x male thread | Bronze                 | See configuration | Confirm for this configuration |
| MCF065         | Instantaneous female coupling x female thread      | Confirm with quotation | See configuration | Confirm for this configuration |
| MCMB065        | Bronze instantaneous male coupling x female thread | Bronze                 | See configuration | Confirm for this configuration |
| MCA065X040/SET | Aluminium instantaneous hose coupling set - 40 mm  | Aluminium              | See configuration | Confirm for this configuration |
| MCA065X045/SET | Aluminium instantaneous hose coupling set - 45 mm  | Aluminium              | See configuration | Confirm for this configuration |
| MCA065X050/SET | Aluminium instantaneous hose coupling set - 50 mm  | Aluminium              | See configuration | Confirm for this configuration |
| MCA065X065/SET | Aluminium instantaneous hose coupling set - 65 mm  | Aluminium              | See configuration | Confirm for this configuration |

Pressure values, where given, apply only to the listed configuration and its specified operating conditions. Confirm the complete assembly, temperature and conveyed medium. Dust closures require explicit pressure-service approval.

**Application & quotation checklist**

Coupling type, size and mating half; Medium, pressure and temperature; Body material and seal compound; Hose tail, thread, flange or weld connection

## Request a quotation

admin@africanhosesolutions.co.za | 010 065 3872

Provide the part code, size, quantity, required configuration and application. Include a drawing or photograph where available.

Ratings apply only to the specified product and configuration. Confirm fluid compatibility, temperature, pressure transients, installation and complete assembly suitability. Ordering references do not establish interchangeability.