

HOSE FITTINGS & ADAPTORS

DW_M - Self Centering Bonded Seal - Metric

Connection components selected by thread, sealing form, dimensions and operating duty.

Ordering references: DW-06M / DW-08M / DW-10M / DW-12M / DW-14M / DW-16M / DW-18M / DW-20M / DW-22M / DW-24M / DW-26M / DW-30M / DW-36M

DW_M bonded seals - German metric reference configurations / column group 1 of 2

Part code	Reference ()	Self-centering reference ()	Alternative reference ()	Dimension A (as labelled) (mm)	Dimension B (as labelled) (mm)	Dimension C (as labelled) (mm)	Dimension D (as labelled) (mm)
DW-06M	206	606	PPM6	10.0	8.0	6.7	0.3
DW-06M	207	607	PPM6	11.0	8.2	6.7	0.3
DW-08M	212	612	PPM8	13.0	10.0	8.7	0.3
DW-08M	213	613	PPM8	14.0	10.4	8.7	0.3
DW-10M	216	616	PPM10	15.88	12.0	10.35	0.4
DW-10M	217	617	PPM10	16.0	12.4	10.7	0.4
DW-10M	218	618	PPM10	18.0	12.4	10.7	0.4
DW-12M	222	622	PPM12	18.0	14.3	12.7	0.4
DW-12M	223	623	PPM12	20.0	14.4	12.7	0.4
DW-14M	227	627	PPM14	22.0	16.4	14.7	0.4
DW-16M	229	629	PPM16	24.0	18.4	16.7	0.4
DW-18M	232	632	PPM18	26.0	20.4	18.7	0.4
DW-20M	233	633	PPM20	28.0	22.5	20.7	0.4
DW-22M	236	636	PPM22	30.0	24.4	22.7	0.4
DW-22M	237	Confirm	PPM22	30.0	24.4	22.7	0.4
DW-24M	238	638	PPM24	32.0	26.4	24.7	0.4

DW_M bonded seals - German metric reference configurations / column group 1 of 2

Part code	Reference ()	Self-centering reference ()	Alternative reference ()	Dimension A (as labelled) (mm)	Dimension B (as labelled) (mm)	Dimension C (as labelled) (mm)	Dimension D (as labelled) (mm)
DW-26M	239	639	PPM26	35.0	28.4	26.7	0.4
DW-30M	242	642	PPM30	39.0	33.0	31.0	0.4
DW-36M	245	645	PPM36	46.0	38.8	36.7	0.4

Identifying columns are repeated. Read all column groups together for the complete row specification.

DW_M bonded seals - German metric reference configurations / column group 2 of 2

Part code	Reference ()	Dimension E (as labelled) (mm)	Dimension F (as labelled) (mm)
DW-06M	206	1.0	4.7
DW-06M	207	1.0	4.7
DW-08M	212	1.0	6.4
DW-08M	213	1.0	6.4
DW-10M	216	2.0	8.56
DW-10M	217	1.5	8.05
DW-10M	218	1.5	8.05
DW-12M	222	1.5	9.73
DW-12M	223	1.5	9.73
DW-14M	227	1.5	11.38
DW-16M	229	1.5	13.41
DW-18M	232	1.5	14.76
DW-20M	233	1.5	16.76
DW-22M	236	2.0	18.74
DW-22M	237	3.0	Confirm

DW_M bonded seals - German metric reference configurations / column group 2 of 2

Part code	Reference ()	Dimension E (as labelled) (mm)	Dimension F (as labelled) (mm)
DW-24M	238	2.0	20.11
DW-26M	239	2.0	22.3
DW-30M	242	2.0	25.7
DW-36M	245	2.0	31.1

Identifying columns are repeated. Read all column groups together for the complete row specification.

Dimensions and ratings apply to the exact configuration shown. Match the connection, material, seal and operating conditions before selection.

DW_M bonded seals - PM1000 metric reference configurations / column group 1 of 2

Part code	Reference ()	Self-centering reference ()	Metric size ()	Dimension A (as labelled) (mm)	Dimension B (as labelled) (mm)	Dimension C (as labelled) (mm)	Dimension D (as labelled) (mm)
DW-06M	3099	4099	M6	10.0	8.0	7.4	6.0
DW-08M	3138	4138	M8	14.0	11.0	10.0	8.0
DW-10M	3076	4076	M10	17.0	13.0	12.0	10.0
DW-12M	3077	4077	M12	19.0	16.0	15.0	12.0
DW-14M	3063	4063	M14	22.0	18.0	17.0	14.0
DW-16M	3078	4078	M16	24.0	20.0	19.0	16.0
DW-18M	3064	4064	M18	27.0	22.0	21.0	18.0
DW-20M	3079	4079	M20	30.0	25.0	24.0	20.0
DW-22M	3098	4098	M22	32.0	27.0	26.0	22.0
DW-24M	3080	4080	M24	36.0	29.0	28.0	24.0
DW-26M	3065	4065	M26	35.0	30.5	30.0	26.0

Identifying columns are repeated. Read all column groups together for the complete row specification.

DW_M bonded seals - PM1000 metric reference configurations / column group 2 of 2

Part code	Dimension E (as labelled) (mm)	Dimension F (as labelled) (mm)	Dimension H (as labelled) (mm)
DW-06M	1.0	0.4	4.7
DW-08M	1.0	0.4	6.4
DW-10M	1.5	0.5	8.56
DW-12M	1.5	0.5	9.73
DW-14M	1.5	0.5	11.38
DW-16M	1.5	0.5	13.41
DW-18M	2.0	0.5	14.76
DW-20M	2.0	0.5	16.76
DW-22M	2.0	0.5	18.74
DW-24M	2.0	0.5	20.11
DW-26M	2.0	0.5	22.3

Identifying columns are repeated. Read all column groups together for the complete row specification.

Dimensions and ratings apply to the exact configuration shown. Match the connection, material, seal and operating conditions before selection.

Construction & application

Parameter	Specification
Configuration selection	Reference-specific configuration required; preserve all rows for a shared bare code.

Operating limits apply to the selected construction and configuration. Confirm the medium, temperature, pressure and end connections for the complete assembly.

Application & quotation checklist

Thread standard, size and sealing form; Hose construction or mating connection; Material and pressure rating; Straight, elbow, tee or special configuration

Request a quotation

admin@africanhosesolutions.co.za | 010 065 3872

Provide the part code, size, quantity, required configuration and application. Include a drawing or photograph where available.

Ratings apply only to the specified product and configuration. Confirm fluid compatibility, temperature, pressure transients, installation and complete assembly suitability. Ordering references do not establish interchangeability.