

## HOSE FITTINGS &amp; ADAPTORS

# J90 - JIC HOSE FITTING - 90° FEMALE

Connection components selected by thread, sealing form, dimensions and operating duty.

Ordering references: X07J90S04 / X08J90S04 / X09J90S04 / X09J90S06 / X10J90S06 / X12J90S06 / X12J90S08 / X14J90S08 / X14J90S10 / X17J90S08 / X17J90S10 / X17J90S12 / X19J90S12 / X21J90S12 / X21J90S16 / X26J90S16 / X26J90S20 / X30J90S24 / X40J90S32

## J90 - JIC HOSE FITTING - 90° FEMALE

| Part code | JIC thread size (in) | Dash (-) | Hose tail (in) |
|-----------|----------------------|----------|----------------|
| X07J90S04 | 7/16                 | -4       | 1/4            |
| X08J90S04 | 1/2                  | -5       | 1/4            |
| X09J90S04 | 9/16                 | -6       | 1/4            |
| X09J90S06 | 9/16                 | -6       | 3/8            |
| X10J90S06 | 5/8 SAE              | -7       | 3/8            |
| X12J90S06 | 3/4                  | -8       | 3/8            |
| X12J90S08 | 3/4                  | -8       | 1/2            |
| X14J90S08 | 7/8                  | -10      | 1/2            |
| X14J90S10 | 7/8                  | -10      | 5/8            |
| X17J90S08 | 1 1/16               | -12      | 1/2            |
| X17J90S10 | 1 1/16               | -12      | 5/8            |
| X17J90S12 | 1 1/16               | -12      | 3/4            |
| X19J90S12 | 1 3/16               | -14      | 3/4            |
| X21J90S12 | 1 5/16               | -16      | 3/4            |
| X21J90S16 | 1 5/16               | -16      | 1              |
| X26J90S16 | 1 5/8                | -20      | 1              |
| X26J90S20 | 1 5/8                | -20      | 1 1/4          |
| X30J90S24 | 1 7/8                | -24      | 1 1/2          |
| X40J90S32 | 2 1/2                | -32      | 2              |

Dimensions and ratings apply to the exact configuration shown. Match the connection, material, seal and operating conditions before selection.

## Application &amp; quotation checklist

Thread standard, size and sealing form; Hose construction or mating connection; Material and pressure rating; Straight, elbow, tee or special configuration

## Request a quotation

admin@africanhosesolutions.co.za | 010 065 3872

Provide the part code, size, quantity, required configuration and application. Include a drawing or photograph where available.

Ratings apply only to the specified product and configuration. Confirm fluid compatibility, temperature, pressure transients, installation and complete assembly suitability. Ordering references do not establish interchangeability.