

HOSE FITTINGS & ADAPTORS

QCPF - PLASTIC PLUGS FOR QUICK RELEASE COUPLERS

Connection components selected by thread, sealing form, dimensions and operating duty.

Ordering references: QCPF-02 / QCPF-03 / QCPF-04 / QCPF-05 / QCPF-06

[qcpf-coupling-dust-protectors](#)

Part code	Coupling family	DNP size	ISO interface size	Dimension D as labelled (mm)	Dimension D1 as labelled (mm)	Weight
QCPF-02	Ball Type	06	6.3	22.0	19.5	15.0
QCPF-03	Ball Type	10	10.0	26.0	24.5	18.0
QCPF-04	Ball Type	13	12.5	29.0	26.0	21.0
QCPF-05	Ball Type	20	19.0	37.0	33.0	43.0
QCPF-06	Ball Type	25	25.0	41.0	39.0	56.0
QCPF-02	Pin Type	06	6.3	17.5	17.5	8.0
QCPF-03	Pin Type	10	10.0	23.5	22.0	16.0
QCPF-04	Pin Type	13	12.5	29.0	26.0	21.0
QCPF-05	Pin Type	20	19.0	36.5	36.0	39.0
QCPF-06	Pin Type	25	25.0	42.0	42.0	47.0
QCPF-02	Flat Face	06	6.3	26.0	20.0	13.0
QCPF-03	Flat Face	13	10.0	27.5	26.0	15.0
QCPF-04	Flat Face	20	12.5	35.0	31.5	26.0
QCPF-05	Flat Face	25	19.0	43.0	35.0	41.0

Dimensions and ratings apply to the exact configuration shown. Match the connection, material, seal and operating conditions before selection.

qcpf-coupling-dust-protectors - construction & conditions

Parameter	Specification
Material	Injection-moulded PVC
Configuration	male dust cap with retaining chain

Dimensions and ratings apply to the exact configuration shown. Match the connection, material, seal and operating conditions before selection.

Application & quotation checklist

Thread standard, size and sealing form; Hose construction or mating connection; Material and pressure rating; Straight, elbow, tee or special configuration

Request a quotation

admin@africanhosesolutions.co.za | 010 065 3872

Provide the part code, size, quantity, required configuration and application. Include a drawing or photograph where available.

Ratings apply only to the specified product and configuration. Confirm fluid compatibility, temperature, pressure transients, installation and complete assembly suitability. Ordering references do not establish interchangeability.