

HYDRAULIC HOSE & PROTECTION

Fire Sleeving

Hose construction and size selected to match the fluid, operating duty and installation.

Construction & technical characteristics

Characteristic	Specification
Outer cover	custom-compounded silicone rubber
Material	High-bulk braided glass fibre with silicone rubber coating

Ordering references: FJ-15MM / FJ-22MM / FJ-32MM / FJ-40MM / FJ-50MM / FJ-55MM / FJ-70MM

Accessory dimensions & configuration

Part code	ID (mm)	Roll length m
FJ-15MM	15	20
FJ-22MM	22	20
FJ-32MM	32	20
FJ-40MM	40	20
FJ-50MM	50	15
FJ-55MM	55	15
FJ-70MM	70	15

External protection is selected by hose dimensions, installation environment and protection function. Hose working and burst pressures do not apply to external sleeves or guards.

Application & quotation checklist

Inside diameter and overall length; Working pressure and pressure peaks; Fluid and operating temperature; End connections, orientation and routing

Request a quotation

admin@africanhosesolutions.co.za | 010 065 3872

Provide the part code, size, quantity, required configuration and application. Include a drawing or photograph where available.

Ratings apply only to the specified product and configuration. Confirm fluid compatibility, temperature, pressure transients, installation and complete assembly suitability. Ordering references do not establish interchangeability.