

INDUSTRIAL & SPECIALIST HOSE

Food & Beverage Hose

Food-contact duty subject to the required declaration and medium.

Ordering references: T-452 LH

Non-toxic steel-wire-reinforced PVC liquid-transfer hose

configuration	Inside diameter (mm)	Outside diameter (mm)	Working pressure (bar)	Burst pressure (bar)	Mass (kg/m)	Roll length (m)
Non-toxic steel-wire-reinforced PVC liquid-transfer hose	20	26	5	15	0.35	30
Non-toxic steel-wire-reinforced PVC liquid-transfer hose	25	31	5	15	0.533	30
Non-toxic steel-wire-reinforced PVC liquid-transfer hose	32	39	4	12	0.65	30
Non-toxic steel-wire-reinforced PVC liquid-transfer hose	38	47	4	12	0.8	30
Non-toxic steel-wire-reinforced PVC liquid-transfer hose	50	59	4	12	1.25	30
Non-toxic steel-wire-reinforced PVC liquid-transfer hose	75	84	3	9	1.75	30

Steel-wire-reinforced PVC liquid-transfer hose. Check the exact food/chemical medium and cleaning conditions for the selected assembly. Food-contact suitability requires the relevant current documentation.

Non-toxic steel-wire-reinforced PVC liquid-transfer hose - construction & conditions

Parameter	Specification
Tube	Transparent plasticised PVC
Reinforcement	Steel wire
Cover	Transparent
Temperature range c	-5 / 60

Non-toxic steel-wire-reinforced PVC liquid-transfer hose - construction & conditions

Parameter	Specification
Service	Liquid food and chemical suction/delivery as described by supplier
Food contact status	No named food-contact standard or specific dairy/CIP compatibility certificate supplied

Steel-wire-reinforced PVC liquid-transfer hose. Check the exact food/chemical medium and cleaning conditions for the selected assembly. Food-contact suitability requires the relevant current documentation.

T-452 LH named series specification

Size reference	Named series	Id min mm	Id max mm	Working pressure bar	Temperature min c	Temperature max c	Standard length options m	Safety factor
T-452 LH	T-452 LH	13	76	10	-30	80	20 / 30 / 60	3

T-452 LH liquid-food and beverage hose. Confirm alcohol content and cleaning chemistry for the selected liner. No 50% ABV suitability is established. A bore range does not identify every orderable size.

T-452 LH named series specification - construction & conditions

Parameter	Specification
Tube	White NR
Reinforcement	Textile cords plus embedded steel helix
Cover	Red SBR/EPDM
Application	Liquid-food/beverage transfer; text includes suction/delivery

T-452 LH liquid-food and beverage hose. Confirm alcohol content and cleaning chemistry for the selected liner. No 50% ABV suitability is established. A bore range does not identify every orderable size.

Non-toxic steel-wire-reinforced PVC liquid-transfer hose

Parameter	Specification
Configurations	Non-toxic steel-wire-reinforced PVC liquid-transfer hose - Only the named construction; other codes or constructions require their own specification.

Steel-wire-reinforced PVC liquid-transfer hose. Check the exact food/chemical medium and cleaning conditions for the selected assembly. Food-contact suitability requires the relevant current documentation.

T-452 LH named series specification

Parameter	Specification
Tube	White NR - Only the named construction; other codes or constructions require their own specification.
Reinforcement	Textile cords plus embedded steel helix - Only the named construction; other codes or constructions require their own specification.
Cover	Red SBR/EPDM - Only the named construction; other codes or constructions require their own specification.
Application	Liquid-food/beverage transfer; text includes suction/delivery - Only the named construction; other codes or constructions require their own specification.

T-452 LH liquid-food and beverage hose. Confirm alcohol content and cleaning chemistry for the selected liner. No 50% ABV suitability is established. A bore range does not identify every orderable size.

Application & quotation checklist

Medium and concentration; Inside diameter and length; Pressure or vacuum and temperature; End connections and electrical requirements

Request a quotation

admin@africanhosesolutions.co.za | 010 065 3872

Provide the part code, size, quantity, required configuration and application. Include a drawing or photograph where available.

Ratings apply only to the specified product and configuration. Confirm fluid compatibility, temperature, pressure transients, installation and complete assembly suitability. Ordering references do not establish interchangeability.