

INDUSTRIAL & SPECIALIST HOSE

Slurry & Sand Delivery Hose

Abrasion-led slurry and sand transport.

Slurry

Parameter	Specification
Manufacturing mode	Project-engineered hand-built slurry/elephant hose
Verified applications	Mining slurry/abrasives / Agricultural water / Concrete placement
End options	Built-in flanges / Open ends with clamp-on fittings
Design definition	Diameter / Length / Pressure/vacuum / Flange type/drilling / Liner material/thickness
Numeric limits	Defined by approved project specification; no public universal diameter/pressure envelope stated

Custom engineered construction for the selected application. Custom dimensions and operating limits are set by the approved design. A manufacturing range is not a rating for every hose in that range. Define bore,length,medium,temperature,working pressure,vacuum,liner and end connections in the quotation.

Black NBR abrasion-resistant layflat hose

Parameter	Specification
Configurations	Black NBR abrasion-resistant layflat hose / custom hand-built rubber hose manufacturing envelope - Only the named construction; other codes or constructions require their own specification.

Black NBR abrasion-resistant layflat hose Dimensions and ratings apply to the named construction or exact code shown. Select pressure, temperature, medium and end fittings together for the finished assembly. Custom dimensions and operating limits are set by the approved design. A manufacturing range is not a rating for every hose in that range.

Application & quotation checklist

Medium and concentration; Inside diameter and length; Pressure or vacuum and temperature; End connections and electrical requirements

Request a quotation

admin@africanhosesolutions.co.za | 010 065 3872

Provide the part code, size, quantity, required configuration and application. Include a drawing or photograph where available.

Ratings apply only to the specified product and configuration. Confirm fluid compatibility, temperature, pressure transients, installation and complete assembly suitability. Ordering references do not establish interchangeability.