

PUMPS, MOTORS & POWER PACKS

2SPA - GROUP 2 GEAR PUMPS

Hydraulic drive components selected to the required flow, pressure and mounting arrangement.

Ordering references: 2SPA - 11.0 / 2SPA - 14.0 / 2SPA - 16.0 / 2SPA - 19.0 / 2SPA - 22.0 / 2SPA - 26.0 / 2SPA - 4.0 / 2SPA - 6.0 / 2SPA - 8.0

2SPA existing-code gear-pump ratings

Part code	Displacement (cm ³ /rev)	Continuous maximum pressure (bar)	Peak pressure (bar)	Maximum speed (rpm)	Listed maximum flow (L/min)
2SPA - 4.0	4	280	320	4000	16
2SPA - 6.0	6	280	320	4000	24
2SPA - 8.0	8.5	280	320	3500	29.7
2SPA - 11.0	11	280	320	3500	38.5
2SPA - 14.0	14	270	290	3500	49
2SPA - 16.0	16.5	230	250	3500	57.7
2SPA - 19.0	19.5	210	230	3300	64.3
2SPA - 22.0	22.5	190	210	2800	63
2SPA - 26.0	26	170	190	2500	65

Gear-pump displacement, continuous-pressure limit, peak-pressure limit and speed limit for each exact code. Continuous pressure, peak pressure and maximum speed are separate limits and do not define a simultaneous duty point. Confirm shaft, mounting, ports, rotation, fluid, temperature and duty cycle. The listed flow belongs to this exact model series; it does not establish equivalence with another pump range.

Application & quotation checklist

Required flow or displacement; Operating pressure and duty cycle; Speed, shaft and mounting arrangement; Rotation, fluid and control requirements

Request a quotation

admin@africanhosesolutions.co.za | 010 065 3872

Provide the part code, size, quantity, required configuration and application. Include a drawing or photograph where available.

Ratings apply only to the specified product and configuration. Confirm fluid compatibility, temperature, pressure transients, installation and complete assembly suitability. Ordering references do not establish interchangeability.