PUMPS, MOTORS & POWER PACKS

PF - PORT FLANGES

Hydraulic drive components selected to the required flow, pressure and mounting arrangement.

Ordering references: N-06-26 / N-06-30 / N-08-30 / N-08-40 / N-12-40 / N-12-51 / N-16-51 / N-16-62 / N-20-62 / N-20-72.5 / T-06-35 / T-06-40 / T-08-35 / T-08-40 / T-12-35 / T-12-40 / T-16-40 / T-16X1.5-3510L / T-18X1.5-3512L / T-22X1.5-3515L / T-22X1.5-4015L / T-24X1.5-3516S / T-26X1.5-4018L / T-30X2-4022L / T-36X2-4028L / T90-16X1.5-3510L / T90-18X1.5-3512L / T90-22X1.5-3515L / T90-22X1.5-4015L / T90-24X1.5-3516S / T90-26X1.5-4018L / T90-30X2-4020S / T90-30X2-4022L / T90-36X2-4028L

PF PORT FLANGES exact configuration / column group 1 of 2

Part code	Angle deg (degrees)	Nominal connection size; thread system unspecified	Port flange shape	Port thread reference	labelled port-flange size; geometry unspecified (mm)	size maximum; reference unspecified (mm)
N-06-26	90	3/8	diamond	BSP; parallel/taper not specified	26.0	Confirm
N-06-30	90	3/8	diamond	BSP; parallel/taper not specified	30.0	Confirm
N-08-30	90	1/2	diamond	BSP; parallel/taper not specified	30.0	Confirm
N-08-40	90	1/2	diamond	BSP; parallel/taper not specified	40.0	Confirm
N-12-40	90	3/4	diamond	BSP; parallel/taper not specified	40.0	Confirm
N-12-51	90	3/4	diamond	BSP; parallel/taper not specified	51.0	Confirm
N-16-51	90	1	diamond	BSP; parallel/taper not specified	Confirm	56.0
N-16-62	90	1	diamond	BSP; parallel/taper not specified	62.0	Confirm
N-20-62	90	1-1/4	diamond	BSP; parallel/taper not specified	62.0	Confirm
T-06-35	90	3/8	square	BSP; parallel/taper not specified	35.0	Confirm
T-06-40	90	3/8	square	BSP; parallel/taper not specified	40.0	Confirm
T-08-35	90	1/2	square	BSP; parallel/taper not specified	35.0	Confirm
T-08-40	90	1/2	square	BSP; parallel/taper not specified	40.0	Confirm
T-12-35	90	3/4	square	BSP; parallel/taper not specified	35.0	Confirm
T-12-40	90	3/4	square	BSP; parallel/taper not specified	40.0	Confirm

PF PORT FLANGES exact configuration / column group 1 of 2

Part code	Angle deg (degrees)	Nominal connection size; thread system unspecified	Port flange shape	Port thread reference	labelled port-flange size; geometry unspecified (mm)	size maximum; reference unspecified (mm)
T-16-40	90	1	square	BSP; parallel/taper not specified	40.0	Confirm
T-16X1.5-3510L	0	Confirm	square	M16×1.5	35.0	Confirm
T-18X1.5-3512L	0	Confirm	square	M18×1.5	35.0	Confirm
T-22X1.5-3515L	0	Confirm	square	M22×1.5	35.0	Confirm
T-24X1.5-3516S	0	Confirm	square	M24×1.5	35.0	Confirm
T-22X1.5-4015L	0	Confirm	square	M22×1.5	40.0	Confirm
T-26X1.5-4018L	0	Confirm	square	M26×1.5	40.0	Confirm
T-30X2-4022L	0	Confirm	square	M30×2	40.0	Confirm
T-36X2-4028L	0	Confirm	square	M36×2	40.0	Confirm
T90-16X1.5-3510L	90	Confirm	square	M16×1.5	35.0	Confirm
T90-18X1.5-3512L	90	Confirm	square	M18×1.5	35.0	Confirm
T90-22X1.5-3515L	90	Confirm	square	M22×1.5	35.0	Confirm
T90-24X1.5-3516S	90	Confirm	square	M24×1.5	35.0	Confirm
T90-22X1.5-4015L	90	Confirm	square	M22×1.5	40.0	Confirm
T90-26X1.5-4018L	90	Confirm	square	M26×1.5	40.0	Confirm
T90-30X2-4022L	90	Confirm	square	M30×2	40.0	Confirm
T90-36X2-4028L	90	Confirm	square	M36×2	40.0	Confirm
T90-30X2-4020S	90	Confirm	square	M30×2	40.0	Confirm

Identifying columns are repeated. Read all column groups together for the complete row specification.

PF PORT FLANGES exact configuration / column group 2 of 2

Part code	size minimum; reference unspecified (mm)	Tube od mm	Tube series
N-06-26	Confirm	Confirm	Confirm
N-06-30	Confirm	Confirm	Confirm
N-08-30	Confirm	Confirm	Confirm
N-08-40	Confirm	Confirm	Confirm
N-12-40	Confirm	Confirm	Confirm
N-12-51	Confirm	Confirm	Confirm
N-16-51	51.0	Confirm	Confirm
N-16-62	Confirm	Confirm	Confirm
N-20-62	Confirm	Confirm	Confirm
T-06-35	Confirm	Confirm	Confirm
T-06-40	Confirm	Confirm	Confirm
T-08-35	Confirm	Confirm	Confirm
T-08-40	Confirm	Confirm	Confirm
T-12-35	Confirm	Confirm	Confirm
T-12-40	Confirm	Confirm	Confirm
T-16-40	Confirm	Confirm	Confirm
T-16X1.5-3510L	Confirm	10	L
T-18X1.5-3512L	Confirm	12	L
T-22X1.5-3515L	Confirm	15	L
T-24X1.5-3516S	Confirm	16	S
T-22X1.5-4015L	Confirm	15	L

PF PORT FLANGES exact configuration / column group 2 of 2

Part code	size minimum; reference unspecified (mm)	Tube od mm	Tube series
T-26X1.5-4018L	Confirm	18	L
T-30X2-4022L	Confirm	22	L
T-36X2-4028L	Confirm	28	L
T90-16X1.5-3510L	Confirm	10	L
T90-18X1.5-3512L	Confirm	12	L
T90-22X1.5-3515L	Confirm	15	L
T90-24X1.5-3516S	Confirm	16	S
T90-22X1.5-4015L	Confirm	15	L
T90-26X1.5-4018L	Confirm	18	L
T90-30X2-4022L	Confirm	22	L
T90-36X2-4028L	Confirm	28	L
T90-30X2-4020S	Confirm	20	S

Identifying columns are repeated. Read all column groups together for the complete row specification.

Pump port-flange choices with listed connection and flange-size references. N pattern denotes diamond ports; T pattern denotes square ports. The listed flange-size number does not replace a bolt-pattern drawing. Confirm the pump or motor port face, bolt spacing, port thread, seal and pressure rating. The duplicate ambiguous size choice is omitted.

Application & quotation checklist

Required flow or displacement; Operating pressure and duty cycle; Speed, shaft and mounting arrangement; Rotation, fluid and control requirements

Request a quotation

admin@africanhosesolutions.co.za | 010 065 3872

Provide the part code, size, quantity, required configuration and application. Include a drawing or photograph where available.

Ratings apply only to the specified product and configuration. Confirm fluid compatibility, temperature, pressure transients, installation and complete assembly suitability. Ordering references do not establish interchangeability.