

TUBING, FLANGES & PIPE FITTINGS

D - Cutting Ring

Hydraulic tube connections and installation components selected to the specified interface.

Ordering references: D04LL / D06L/S / D08L/S / D10L/S / D12L/S / D14S / D15L / D16S / D18L / D20S / D22L / D25S / D28L / D30S / D35L / D38S / D42L

D - Cutting Ring

Part code	Mass per100 pieces (kg/100 pieces)	DIN series label	Listed pressure (bar)	Tube outside diameter (mm)
D04LL	Confirm	LL	Confirm	4
D06L/S	Confirm	L/S	Confirm	6
D08L/S	Confirm	L/S	Confirm	8
D10L/S	Confirm	L/S	Confirm	10
D12L/S	Confirm	L/S	Confirm	12
D14S	0.36	S	630.0	14
D15L	0.41	L	315.0	15
D16S	0.41	S	400.0	16
D18L	0.46	L	315.0	18
D20S	0.85	S	400.0	20
D22L	0.6	L	160.0	22
D25S	1.06	S	400.0	25
D28L	0.75	L	160.0	28
D30S	1.6	S	400.0	30
D35L	1.6	L	160.0	35
D38S	2.0	S	315.0	38
D42L	2.1	L	160.0	42

Exact tube-fitting selections by tube outside diameter, series and the connection dimensions shown. Use the exact tube outside diameter, series and stated threads together. Listed pressure is specific to the row; material, seal compound, temperature basis, assembly requirements and installation dimensions require confirmation. Missing values are not inferred from a DIN series or similar part number.

Application & quotation checklist

Standard, nominal size and pressure class; Material grade and wall thickness; Facing, drilling and connection type; Drawing or dimensions of the mating connection

Request a quotation

admin@africanhosesolutions.co.za | 010 065 3872

Provide the part code, size, quantity, required configuration and application. Include a drawing or photograph where available.

Ratings apply only to the specified product and configuration. Confirm fluid compatibility, temperature, pressure transients, installation and complete assembly suitability. Ordering references do not establish interchangeability.