

TUBING, FLANGES & PIPE FITTINGS

EVL - ADJUSTABLE RUN TEE

Hydraulic tube connections and installation components selected to the specified interface.

Ordering references: EVL06L / EVL08L / EVL10L / EVL12L / EVL12S / EVL15L / EVL16S / EVL18L / EVL20S / EVL22L / EVL25S

EVL - ADJUSTABLE RUN TEE

Part code	Adjustable connection	Tube-end thread T1 (metric diameter x pitch (mm))	Second fitting thread T2 (metric diameter x pitch (mm))	DIN series label	Listed pressure (bar)	Tube outside diameter (mm)
EVL06L	Yes	12x1.5	12x1.5	L	315.0	6
EVL08L	Yes	14x1.5	14x1.5	L	315.0	8
EVL10L	Yes	16x1.5	16x1.5	L	315.0	10
EVL12L	Yes	18x1.5	18x1.5	L	315.0	12
EVL12S	Yes	20x1.5	20x1.5	S	630.0	12
EVL15L	Yes	22x1.5	22x1.5	L	315.0	15
EVL16S	Yes	24x1.5	24x1.5	S	400.0	16
EVL18L	Yes	26x1.5	26x1.5	L	315.0	18
EVL20S	Yes	30x2	30x2	S	400.0	20
EVL22L	Yes	30x2	30x2	L	160.0	22
EVL25S	Yes	36x2	36x2	S	400.0	25

Exact tube-fitting selections by tube outside diameter, series and the connection dimensions shown. Use the exact tube outside diameter, series and stated threads together. Listed pressure is specific to the row; material, seal compound, temperature basis, assembly requirements and installation dimensions require confirmation. Missing values are not inferred from a DIN series or similar part number.

Application & quotation checklist

Standard, nominal size and pressure class; Material grade and wall thickness; Facing, drilling and connection type; Drawing or dimensions of the mating connection

Request a quotation

admin@africanhosesolutions.co.za | 010 065 3872

Provide the part code, size, quantity, required configuration and application. Include a drawing or photograph where available.

Ratings apply only to the specified product and configuration. Confirm fluid compatibility, temperature, pressure transients, installation and complete assembly suitability. Ordering references do not establish interchangeability.