TUBING, FLANGES & PIPE FITTINGS

KOR - REDUCING STAND PIPE

Hydraulic tube connections and installation components selected to the specified interface.

Ordering references: KOR08/06L / KOR10/08L / KOR12/06L / KOR12/08L / KOR12/10L / KOR15/12L / KOR16/12S / KOR18/10L / KOR18/12L / KOR18/15L / KOR20/12S / KOR22/18L / KOR25/12S / KOR25/20S

KOR - REDUCING STAND PIPE

Part code	Tube-end thread T1 (metric diameter × pitch (mm))	Second fitting thread T2 (metric diameter × pitch (mm))	DIN series label	Listed pressure (bar)	Tube outside diameter (mm)
KOR08/06L	14×1.5	12×1.5	L	315.0	8
KOR10/08L	16×1.5	14×1.5	L	315.0	10
KOR12/06L	18×1.5	12×1.5	L	315.0	12
KOR12/08L	18×1.5	14×1.5	L	315.0	12
KOR12/10L	18×1.5	16×1.5	L	315.0	12
KOR15/12L	22×1.5	18×1.5	L	315.0	15
KOR16/12S	24×1.5	20×1.5	S	400.0	16
KOR18/10L	26×1.5	16×1.5	L	315.0	18
KOR18/12L	26×1.5	18×1.5	L	315.0	18
KOR18/15L	26×1.5	22×1.5	L	315.0	18
KOR20/12S	30×2	20×1.5	S	400.0	20
KOR22/18L	30×2	26×1.5	L	315.0	22
KOR25/12S	36×2	20×1.5	S	400.0	25
KOR25/20S	36×2	30×2	S	400.0	25

Exact tube-fitting selections by tube outside diameter, series and the connection dimensions shown. Use the exact tube outside diameter, series and stated threads together. Listed pressure is specific to the row; material, seal compound, temperature basis, assembly requirements and installation dimensions require confirmation. Missing values are not inferred from a DIN series or similar part number.

Application & quotation checklist

Standard, nominal size and pressure class; Material grade and wall thickness; Facing, drilling and connection type; Drawing or dimensions of the mating connection

Request a quotation

admin@africanhosesolutions.co.za | 010 065 3872

Provide the part code, size, quantity, required configuration and application. Include a drawing or photograph where available.

Ratings apply only to the specified product and configuration. Confirm fluid compatibility, temperature, pressure transients, installation and complete assembly suitability. Ordering references do not establish interchangeability.