

TUBING, FLANGES & PIPE FITTINGS

WSV - BULKHEAD ELBOW

Hydraulic tube connections and installation components selected to the specified interface.

Ordering references: WSV06L / WSV08L / WSV08S / WSV10L / WSV10S / WSV12L / WSV12S / WSV15L / WSV16S / WSV18L / WSV22L

WSV - BULKHEAD ELBOW

Part code	Fitting angle (degrees)	Tube-end thread T1 (metric diameter × pitch (mm))	Second fitting thread T2 (metric diameter × pitch (mm))	Mass per100 pieces (kg/100 pieces)	DIN series label	Listed pressure (bar)	Tube outside diameter (mm)
WSV06L	90	12×1.5	12×1.5	7.0	L	315.0	6
WSV08L	90	14×1.5	14×1.5	10.0	L	315.0	8
WSV08S	90	16×1.5	16×1.5	13.0	S	630.0	8
WSV10L	90	16×1.5	16×1.5	13.0	L	315.0	10
WSV10S	90	18×1.5	18×1.5	20.0	S	630.0	10
WSV12L	90	18×1.5	18×1.5	19.0	L	315.0	12
WSV12S	90	20×1.5	20×1.5	24.0	S	630.0	12
WSV15L	90	22×1.5	22×1.5	28.0	L	315.0	15
WSV16S	90	24×1.5	24×1.5	37.0	S	400.0	16
WSV18L	90	26×1.5	26×1.5	38.0	L	315.0	18
WSV22L	90	30×2	30×2	49.0	L	160.0	22

Exact tube-fitting selections by tube outside diameter, series and the connection dimensions shown. Use the exact tube outside diameter, series and stated threads together. Listed pressure is specific to the row; material, seal compound, temperature basis, assembly requirements and installation dimensions require confirmation. Missing values are not inferred from a DIN series or similar part number.

Application & quotation checklist

Standard, nominal size and pressure class; Material grade and wall thickness; Facing, drilling and connection type; Drawing or dimensions of the mating connection

Request a quotation

admin@africanhosesolutions.co.za | 010 065 3872

Provide the part code, size, quantity, required configuration and application. Include a drawing or photograph where available.

Ratings apply only to the specified product and configuration. Confirm fluid compatibility, temperature, pressure transients, installation and complete assembly suitability. Ordering references do not establish interchangeability.