

ASSEMBLY & WORKSHOP EQUIPMENT

D16 Hand Crimper

Assembly equipment selected to the hose range, tooling and workshop requirements.

Ordering references: d16hc

D16HC Hand Crimper Specifications / column group 1 of 2

Part code	Crimp diameter max mm	Crimp diameter min mm	Drive	Hose construction reference	Max crimping force kn	Max hose id inch	Max machine circuit pressure bar	Model reference
d16hc	45	4	hand pump	2SN	955	1	700	D16HC

Identifying columns are repeated. Read all column groups together for the complete row specification.

D16HC Hand Crimper Specifications / column group 2 of 2

Part code	Net mass excluding oil kg	max opening mm	Standard die set count
d16hc	25	20	6

Identifying columns are repeated. Read all column groups together for the complete row specification.

Hand-operated hose crimper configuration. The pressure figure is the machine hydraulic-circuit limit, not the working pressure of a finished hose assembly. Confirm the supplied model revision, pump, dies, hose construction and fittings. Use the approved hose/fitting crimp specification; diameter range alone does not qualify every assembly.

Application & quotation checklist

Hose and fitting range; Required assembly capacity; Power supply and operating location; Tooling, testing and support requirements

Request a quotation

admin@africanhosesolutions.co.za | 010 065 3872

Provide the part code, size, quantity, required configuration and application. Include a drawing or photograph where available.

Ratings apply only to the specified product and configuration. Confirm fluid compatibility, temperature, pressure transients, installation and complete assembly suitability. Ordering references do not establish interchangeability.