

ASSEMBLY & WORKSHOP EQUIPMENT

D20 Electric Crimper

Assembly equipment selected to the hose range, tooling and workshop requirements.

Ordering references: d20

D20 Electric Crimper Catalogue Configuration / column group 1 of 4

Part code	Additional opening mm	Control	Crimp diameter max mm	Crimp diameter min mm	Die series	Gross mass kg	Hose construction reference	Machine height mm
d20	25	semi-automatic	61	10	D20	227	4SH	1340

Identifying columns are repeated. Read all column groups together for the complete row specification.

D20 Electric Crimper Catalogue Configuration / column group 2 of 4

Part code	Machine length mm	Machine width mm	Master die diameter mm	Master die length mm	Max crimping force kn	Max hose id inch	Max opening without dies mm	Model reference
d20	840	600	84	80	1370	1-1/2	109	D20

Identifying columns are repeated. Read all column groups together for the complete row specification.

D20 Electric Crimper Catalogue Configuration / column group 3 of 4

Part code	Motor power kw	Net mass kg	Oil tank capacity l	Package height mm	Package length mm	Package width mm	Single phase voltage options v	crimps per hour options (assemblies/hour (reference))
d20	3	204	32	890	925	765	110 / 115 / 220 / 230 / 240	600 / 850

Identifying columns are repeated. Read all column groups together for the complete row specification.

D20 Electric Crimper Catalogue Configuration / column group 4 of 4

Part code	cycle time 10mm s	Three phase voltage options v
d20	3.6	200 / 220 / 380 / 440

Identifying columns are repeated. Read all column groups together for the complete row specification.

Dimensions and operating capability for the specified machine build. Specifications describe the selected machine configuration. Confirm the supplied revision, base/stand, electrical drive, dies, opening geometry and installation dimensions with the quotation. Cycle times and hourly outputs are listed reference figures, not a guaranteed production rate for every hose assembly. Machine force and hose-type capacity do not establish an approved crimp setting for a hose/fitting combination.

[Application & quotation checklist](#)

Hose and fitting range; Required assembly capacity; Power supply and operating location; Tooling, testing and support requirements

Request a quotation

admin@africanhosesolutions.co.za | 010 065 3872

Provide the part code, size, quantity, required configuration and application. Include a drawing or photograph where available.

Ratings apply only to the specified product and configuration. Confirm fluid compatibility, temperature, pressure transients, installation and complete assembly suitability. Ordering references do not establish interchangeability.